ASSEMBLY OF APRILAIRE MEDIA IN MEDIA HOUSING




FIGURE 2




FIGURE 3




FIGURE 4




FIGURE 5

- 1. Loosen four screws on grille assembly (Figure 1).
- 2. Compress safety catches and pull grille assembly toward you to remove. NOTE: Media housing remains attached to grille. (See Figure 1.)
- 3. Remove Aprilaire media and end panel seals from their carton. Remove eight pleat spacers from cartons.
- 4. Note the position of the two black holding brackets (A), Figure 2, and remove.
- 5. Place the two end panel seals (B), Figure 3 in the end panels (C).
- Place slots in one cardboard flap (D), Figure 4, over the plastic hooks (E) starting at far end of the media housing.
- Grasp Aprilaire media (F) on both sides (Figure 5) and expand to near end carefully placing slots in the cardboard flap (D) over the plastic hooks (E). Center media in housing.
- 8. Place holding brackets (A) (Figure 2) over the cardboard flaps of the media and position in the same manner as when removed in Step 4. Center the holding brackets with ends of housing.
- 9. Carefully install the eight pleat spacers (G) so that each spacer finger separates one media pleat. The ends of the pleat spacers align with notches and snap into slots of holding brackets. (See exploded view.)
- 10. Close end panels (C). Snap latches (H) in place by grasping latches with fingers and inside corners of holding brackets with thumbs and squeeze.

FINAL ASSEMBLY

Compress safety catches and set grille assembly into unit, making sure rounded edge is toward end of unit. (See Figure 1.) Align fasteners with receptacles and tighten four screws.

